



MATERIAL SAFETY DATA SHEET

SECTION 1 - MANUFACTURER OR SUPPLIER DATA

MSDS NUMBER

101872

MANUFACTURER'S NAME & MAILING ADDRESS U S Chemical Corporation 316 Hart Street Watertown, Wisconsin 53094 USA	PREPARED BY D. E. Kenas	SIGNATURE <i>David E. Kenas</i>
	TITLE Quality Assurance Manager	DATE 12-20-99
EMERGENCY TELEPHONE NO. (24 HOUR SERVICE) Medical Emergency ONLY: 1-800-851-7145 Ext. 075	PRODUCT INFORMATION TELEPHONE NO. (8 AM TO 5 PM CST. MON - FRI) Product Information: 1-800-558-9566	

SECTION 2 - IDENTITY OF MATERIAL

PRODUCT NAME FRYER CLEANER			
PRODUCT DESCRIPTION Alkaline Deep Fry Cleaner and Heavy Duty Degreaser		FORMULA Proprietary Blend	CHEMICAL FAMILY N.A.
REGULATED IDENTIFICATION	DOT PROPER SHIPPING NAME CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM HYDROXIDE)		
	SHIPPING ID NUMBER UN3262	PACKING GROUP II	HAZARD CLASS 8 (CORROSIVE MATERIAL)

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT N.A.	SPECIFIC GRAVITY (H ₂ O = 1) N.A.	PHYSICAL FORM Granular Powder	COLOR White
VAPOR PRESSURE (mm Hg) N.A.	MELTING POINT N.A.	SOLUBILITY IN WATER Moderate	SCENT None Added
VAPOR DENSITY (AIR = 1) N.A.	EVAPORATION RATE (BUTYL ACETATE = 1) N.A.	pH 2500 ppm SOLUTION 12.2	pH CONCENTRATE N.A.
OTHER N.A.			

SECTION 4 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS (CHEMICAL NAME: COMMON NAME)	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	PERCENT WT/WT
Sodium Hydroxide: Caustic Soda CAS Registry Number 1310-73-2	2 mg/m3 Ceiling Limit	2 mg/m3 Ceiling Limit	None	15.0-40.0
Sodium Metasilicate CAS Registry Number 6834-92-0	Not Established	Not Established	2 mg/m3 Ceiling Limit (PQ Corporation)	3.0-7.0
Sodium Carbonate: Soda Ash CAS Registry Number 497-19-8	Not Established	Not Established	Not Established	40.0-70.0

This product contains no other ingredient considered hazardous according to the criteria of 29 CFR 1910.1200, OSHA. However, this product contains chemicals which may be subject to reporting requirements according to the criteria of SARA Title III, 40 CFR, Part 370, Section 311 and Section 312.

STATE RIGHT TO KNOW INFORMATION

THIS PRODUCT CONTAINS: SODIUM CARBONATE/497-19-8, SODIUM HYDROXIDE/1310-73-2, SODIUM METASILICATE/6834-92-0, SODIUM TRIPOLYPHOSPHATE/7758-29-4

NFPA RATING: Health-3/Flammability-0/Reactivity-1 See Section 5 for Protective Equipment.

HMS RATING: Health-3/Flammability-0/Reactivity-1 See Section 5 for Protective Equipment.

CARCINOGENICITY:

This product does not contain any known carcinogens or anticipated carcinogens according to the criteria of the NTP Annual Report on Carcinogens, IARC Monographs, and OSHA 29 CFR 1910, Subpart Z.

(CONTINUED IN SECTIONS 5 TO 8)

SECTION 5 - SAFE USAGE DATA

PROTECTIVE EQUIPMENT TYPES	EYES Safety glasses, safety goggles, and an eye-wash station.	
	RESPIRATORY Dust mask if handling creates air-borne dust.	GLOVES Rubber or Neoprene.
	OTHER Wear full-cover protective clothing to prevent repeated or prolonged contact.	
VENTILATION	GENERAL MECHANICAL Satisfactory. Maintain adequate ventilation. Keep levels below recommended TLV.	
	LOCAL EXHAUST Not ordinarily needed. Avoid inhalation of dust containing this product.	
PRECAUTIONS	HANDLING & STORAGE Follow all label directions. Instruct personnel about proper use, hazards, precautions, and first-aid measures. Avoid inhalation, ingestion and contact with skin and eyes.	
	Do not use on aluminum. Rotate stock regularly. Handle carefully to avoid damaging container. Keep container closed. Recommended storage temperature below 100°F. Keep out of children's reach.	

SECTION 6 - HEALTH HAZARD DATA

EFFECTS OF EXPOSURE	INHALATION	Corrosive. Inhalation of dust or mist may cause irritation to nose, throat and mucous membranes, pulmonary irritation, pulmonary edema, tissue damage and chemical burns.
	INGESTION	Corrosive. Harmful or fatal if swallowed. May cause nausea, vomiting, and severe tissue damage to digestive tract. Corrosive to mouth, throat, stomach and to other tissues.
	SKIN & EYES	SKIN: Corrosive. Contact may cause severe irritation, dermatitis, and chemical burns. EYES: Corrosive. Causes eye burns. May cause temporary or permanent vision loss and blindness.
	ACUTE & CHRONIC	ACUTE: Corrosive to all body tissues. Harmful skin contact may not cause immediate pain. Permanent eye damage may result without immediate first aid treatment. CHRONIC: None Known.
ROUTES OF ENTRY	INGESTION-X SKIN ABSORPTION-X SKIN-X EYES-X INHALATION-X	TARGET ORGANS Eyes, Skin, Respiratory System.

SECTION 7 - PHYSICAL HAZARD DATA

FLAMMABILITY	LEL = N.A. UEL = N.A.	FLASH POINT = N.A.	METHOD USED = N.A.
STABILITY	STABLE	X	CONDITIONS TO AVOID Mixing with any other cleaning product. Mix only with <150°F water. Avoid temperatures above 100° F and high humidity to prevent caking.
	UNSTABLE		HAZARDOUS DECOMPOSITION PRODUCTS Mixing with incompatible materials may produce hydrogen, carbon monoxide, carbon dioxide, and other toxic and irritating fumes.
HAZARDOUS POLYMERIZATION	MAY OCCUR	X	CONDITIONS TO AVOID
	WILL NOT OCCUR		N.A.
INCOMPATIBILITY	MATERIALS TO AVOID Acidic materials, organic chemicals, and various metals (aluminum, magnesium, zinc, tin, brass or bronze) which can generate flammable hydrogen gas.		

SECTION 8 - EMERGENCY RESPONSE DATA

FIRE	EXTINGUISHING MEDIA	For fires in area, use appropriate media. For example: Water spray, dry chemical, carbon dioxide, or alcohol foam.
	SPECIAL PROCEDURES	Use protective clothing and a self-contained breathing apparatus should be worn by fire fighters in areas where product is being stored.
	UNUSUAL HAZARDS	Product may react with some metals such as aluminum, zinc, tin, etc., to release flammable hydrogen gas.
FIRST AID MEASURES	INGESTION: Do not induce vomiting. If patient is conscious and can swallow, administer milk or water. SKIN: Remove contaminated clothes, flood with water for 15 minutes. EYES: Flood with lukewarm (not hot) water poured from a large glass 2 or 3 inches from eyes. Remove contacts. Have patient blink as much as possible while flooding the eyes. Continue for 15 minutes. INHALATION: Move victim to fresh air. Give artificial respiration if patient is not breathing. ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-800-851-7145 Ext 075 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.	
	STEPS TO BE TAKEN	Use proper protective equipment. Carefully sweep up and shovel into dry containers without raising dust. Cover containers and move containers out of spill area. Flush area with water and follow with normal clean-up procedures.
SPILLS	Flush area with water and follow with normal clean-up procedures.	
WASTE DISPOSAL METHOD	Comply with all federal, state, and local regulations. Consult state and local authorities for restrictions on disposal of chemical waste. Please recycle empty container whenever possible.	

THE DATA IN THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR PROCESS. THE DATA CONTAINED IS BELIEVED TO BE ACCURATE. HOWEVER, SINCE USE CONDITIONS VARY AND ARE OUTSIDE OUR CONTROL, THE MANUFACTURER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO LIABILITY FOR FAILURE TO FOLLOW PRODUCT USE DIRECTIONS AND SAFETY PRECAUTIONS.